

MODEL NO: RGD-DSP-A01500J-0001

TECHNICAL SPECIFICATIONS:

Display Size: 15 inches

Resolution: 1024 x 768

Working Frequency: 60Hz

Screen Brightness: 350cd/m²

Port: 1*AUDIO、1*MIC、1*GVA、1*DVI、1*HDMI、1*DC12V、1*Power

Material: Aluminum Alloy

Dimension: 400mm*320mm*76mm

Cabinet Color: Silvery white (optional)

Weight: 11.8KG

Mounting Solution: Panel Mount

Working Temperature: -20°C ~ +70°C

Storage Temperature: -20°C ~ +70°C



Electromagnetic Compatibility:

1, Meet MIL-STD-461G (EMC, EMI, EMS, ESD):

CE101 25Hz - 10kHz Conducted Emissions, Audio Frequency Currents, Power leads

CE102 10kHz -10MHz Conducted Emissions, Radio Frequency Potentials, Power leads

CS101 25Hz - 150kHz Conducted Susceptibility, Power Leads

CS106 Conducted Susceptibility, Transients, Power Leads

CS112 Electrostatic Discharge Susceptibility

CS114 4kHz -400MHz Conducted Susceptibility, Bulk Cable injection

CS115 Conducted Susceptibility, Bulk Cable injection, Impulse Excitation

CS116 10kHz - 100MHz Conducted Susceptibility, Damped Sinusoidal Transients, Cables and Power Leads

RE101 25Hz -100kHz Radiated Emissions, Magnetic Field

RE102 10kHz - 18GHz Radiated Emissions, Electric Field

RS101 25Hz - 100kHz Radiated Susceptibility, Magnetic Field

RS103 10kHz - 40GHz Radiated Susceptibility, Electric Field

2, MIL-STD-810F (high and low wide temperature, low pressure, humidity, vibration, shock, salt spray, temperature shock, rain, dust, fungus, solar radiation etc.)

