

# MODEL NO: RGD-KVM-1708HCI-CAT5

## Product Features:

- 1) Integrated 17.3" LED display/keyboard/mouse/switch four-in-one machine
- 2) LED LCD display adjustment function, guide rail with self-locking device
- 2) Support local control, 1000M Intel IP remote control
- 3) Adopts with withdrawing installation design and length can be adjusted to fit the rack space
- 4) Humanized design, can be installed and removed by only one person , which improves the efficiency of the administrator.
- 5) Support a variety of brand industrial computer and the sever, eg: IBM、 DELL、 HP、 SUN、  
Lenovo、 advantech、 EVOC etc.
- 6) Support various operating system: Microsoft、 Linux、 Unix etc.



## TECHNICAL SPECIFICATIONS:

**Computer Connect:** 8 computers, Category 5 network cable 1-100 meters

**port Connector:** USB VGA CAT5 module cable, USB HDMI CAT5 module (optional)

**Control Port Type:** Local USB keyboard and mouse, VGA display, remote IP control (optional)

**Switsh Mode:** OSD Menus, hot keys, buttons

**Hot Keys:** Scroll-Lock / Caps-Lock /Num-Lock / KVM OSD

**LCD:** Size: 17.3" TFT LED, Resolution: 1920\*1080 @60HZ, Max Color: 16.7M,

Brightness: 300nits, Contrast Ratio: 700:1, Pixel Pitch: 380\*215 19:9 / 0.198 x 0.198 mm

**Keyboard/Mouse:** 104 Keys Keyboard with touchpad (with scroll wheel option)

**Power Input:** Built-in power supply: AC100-240V 47-63Hz, 35W, or power adapter: 12V 3.33A. The default AC built-in power supply is shipped

**Actual power consumption:** 18W

**OS:** Microsoft、Linux、 Unix etc. operating system

**Material:** High strength anti-corrosion sheet metal

**Cabinet Color:** High-temperature spray Black

**Dimension:** 450.0mm x 475.0mm x 44.0mm (L x W x H)

**Withdraw Distance:** 45MM

**Opening Height:** 325MM

**Install the cabinet:** 800-1040mm

**Weight:** N.W. 10.75KG, G.W. 16.90KG

**Working Temperature:** 0°C ~ +60°C

**Storage Temperature:** -20°C~ +70°C

**Humidity:** 0%~80%

**Certificate:** FCC/CE/Rohs

